



## ACOUSTIC CEILING

## LAE-AUDIO

### AC 4X6"

<b>CABINET TYPE</b>	<b>BASS-REFLEX</b>
<b>CONSTRUCTION</b>	<b>MULTILAYED PAINTED WOOD CABINET</b>
<b>CONNECTION</b>	<b>N° 02 SPEAKON 4P</b>
<b>BOX VOLUME</b>	<b>78 L.</b>
<b>WOOFER</b>	<b>4X6"</b>
<b>DRIVER</b>	<b>4X1"</b>
<b>TUNING FREQUENCY</b>	<b>62Hz</b>
<b>CROSSOVER FREQUENCY</b>	<b>2,5KHz</b>
<b>NOMINAL IMPEDANCE</b>	<b>8 ohm</b>
<b>MINIMUM IMPEDANCE</b>	<b>6,2 ohm</b>
<b>FREQUENCY RANGE</b>	<b>65-20000 Hz</b>
<b>NOMINAL POWER</b>	<b>400W aes (1)</b>
<b>MAXIMUM POWER HANDLING</b>	<b>800W</b>
<b>SENSITIVITY 1W/1Mt</b>	<b>92db (2)</b>
<b>MAX PEAK SPL</b>	<b>115db (3)</b>
<b>RECOMMENDET AMPLIFIER</b>	<b>300-500W</b>
<b>DIMENSION</b>	<b>Cm. 20,50 X 20,00 X 300,00 (4)</b>
<b>WEIGHT</b>	<b>Kg. 19,00</b>

#### NOTE:

(1) HIGH PASS 60Hz. 24db/octave (55Hz. 48db/octave)

(2) IN EVERY POINT UNDER THE SYSTEM

(3) IN EVERY POINT UNDER THE SYSTEM

(4) N ° 12 POINTS FOR BRACKETS M8

WE RECOMMEND A MAXIMUM DISTANCE OF Mt.1.00 AMONG THE CENTER OF TWO SPEAKERS