



# M808

Power Amplifier

Class A-B Output Stage

## TECHNICAL SPECIFICATION

INPUT	XLR
LINK	XLR
INPUTS SIGNAL	0,775V
INPUTS INPED.	10K
Output Power 8 ohm Wrms	2x450
Output Power 4 ohm Wrms	2x800
Output Power 2 ohm Wrms	no
Output bridge 8 ohm Wrms	1600
Output bridge 4 ohm Wrms	no
Outputs	Speakon + Wire Clamps
DAMPING FACT.	>200
NOISE db.	-101
SLAVE RATE V/ms.	>35
FREQUENCY RES.	25Hz at 20KHz
THD%	1%
POWER REQUIREMENT	1800 W

## PROTECTION

SOFT START	SI
SIGNAL LIMITER	SI
OUTPUT LIMITER	SI
THERMAL PROTECTION	SI
FAULT	SI
FUSE AC	SI

## FRONT PANEL

LED CLI/LIMIT	**
SIGNAL LIMITER	**
LED FAULT	**
LED MONO	*
LED BRIDGE	*
VOLUME	**
MONO	*
BRIDGE	*
POWER	*

## DIMENSION & WEIGHT

RACK HEIGHT	2U
DEPH	370mm
PACKED WEIGHT	16 Kg.

## FEATURES



Amplificatore M808, nuova serie M3  
Uncolored sound, bassa distorsione.

- ° Automatic clip/limiting
- ° Protection over-temperature
- ° thermal short-circuit
- ° over load protection
- ° temperature controlled air cooling

lae s.n.c.

Viale Petrarca 121/B

04100 LATINA

TEL.0773/693756

